

# 屋内照明器具特性

品番 (品名)	SLB15784 + SLK22007 + SLK290	
光源	LLD2421LCB1 ×1	500.0 l m
管理番号	K0193682 (0) DB 1	
BZ分類	BZ1 / 1.4 / BZ2 / 4.5 / BZ3	

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 12 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	85 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	等価発光面積	c m <sup>2</sup>	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	84	87	90	92	94	96	97	98	99
			84	87	90	92	94	96	97	98	99	84	87	90	92	94	96	97	98	99
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	84	87	90	92	94	96	97	98	99	84	87	90
H m	横方向 (A)	縦方向 (B)	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m
	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m	0.53 H m

