

# 屋内照明器具特性

品番 (品名)	SLB15784+SLK22008+SLK290														
光源	LLD3401LCB1 ×1                      700.0 1 m														
管理番号	K0192481 ( 1 ) DR 1														
BZ分類	BZ1														

器具効率	38 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	38 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	31	29	27	26	31	29	27	26	30	28	27	26	30	28	27	26	26		
		0.8	34	32	30	29	34	32	30	29	33	31	30	29	32	31	30	29	28		
		1.0	35	34	32	31	35	33	32	31	34	33	32	31	34	33	32	31	30		
		1.25	37	35	34	33	36	35	34	33	36	34	33	32	35	34	33	32	32		
下方投影面積	c m <sup>2</sup>	1.5	37	36	35	34	37	36	35	34	36	35	34	34	36	35	34	33	33		
		2.0	38	37	36	35	38	37	36	35	37	36	36	35	37	36	35	35	34		
取付高さ	器具間隔最大限		2.5	39	38	37	36	39	38	37	36	38	37	36	37	36	36	35	35		
	横方向 (A)	縦方向 (B)	3.0	39	38	38	37	39	38	37	37	38	38	37	36	37	37	36	35		
H m	0.87 H m	0.86 H m	4.0	40	39	39	38	40	39	38	38	39	38	38	37	38	37	37	36		
			5.0	40	40	39	39	40	39	39	38	39	38	38	38	38	38	38	37	36	
			7.0	40	40	40	39	40	40	39	39	39	39	39	39	38	38	38	37		
			10.0	41	40	40	40	40	40	40	40	39	39	39	39	39	38	38	37		

