

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND5 5 7 1 S W               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED4000_80_5745 ×1 5745.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0160723 (0) DB 1            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ2 / 0.7 / BZ1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |             |                 |                  |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |    |
|--------|-------------|-----------------|------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|----|
| 器具効率   | 100 %       | 天井              | 80 %             |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 % |    |
|        |             | 壁               | 70               | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 % |    |
| 上方光束   | 0 %         | 床               | 10 %             |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 0 % |    |
| 下方光束   | 100 %       | 室指数             | 照明率 ( X0.01) ZCM |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |    |
| 保守率    | 良<br>中<br>否 | 0.76            | 0.6              | 70  | 61  | 55  | 51   | 69  | 61  | 55  | 51   | 67  | 60  | 55  | 51   | 66  | 59 | 54 | 51  | 49 |
|        |             | 0.72            | 0.8              | 80  | 72  | 67  | 63   | 79  | 72  | 67  | 63   | 77  | 71  | 66  | 62   | 75  | 70 | 65 | 62  | 61 |
|        |             | 0.64            | 1.0              | 86  | 79  | 74  | 70   | 85  | 79  | 74  | 70   | 83  | 77  | 73  | 70   | 81  | 76 | 73 | 70  | 68 |
|        |             |                 | 1.25             | 91  | 85  | 80  | 77   | 90  | 84  | 80  | 77   | 88  | 83  | 79  | 76   | 86  | 82 | 78 | 76  | 74 |
| 下方投影面積 |             | cm <sup>2</sup> | 1.5              | 94  | 89  | 84  | 81   | 93  | 88  | 84  | 81   | 91  | 86  | 83  | 80   | 88  | 85 | 82 | 80  | 78 |
| 等価発光面積 |             | cm <sup>2</sup> | 2.0              | 98  | 93  | 90  | 87   | 96  | 93  | 89  | 87   | 94  | 91  | 88  | 86   | 92  | 89 | 87 | 85  | 83 |
| 取付高さ   | 器具間隔最大限     |                 | 2.5              | 100 | 96  | 93  | 91   | 99  | 95  | 93  | 90   | 96  | 94  | 91  | 89   | 94  | 92 | 90 | 88  | 86 |
|        | 横方向 (A)     | 縦方向 (B)         | 3.0              | 101 | 98  | 96  | 93   | 100 | 97  | 95  | 93   | 98  | 96  | 93  | 92   | 96  | 94 | 92 | 91  | 88 |
| Hm     | 1.32Hm      | 1.32Hm          | 4.0              | 103 | 101 | 99  | 97   | 102 | 100 | 98  | 96   | 100 | 98  | 96  | 95   | 98  | 96 | 95 | 93  | 91 |
|        |             |                 | 5.0              | 104 | 102 | 101 | 99   | 103 | 101 | 100 | 98   | 101 | 99  | 98  | 97   | 99  | 97 | 96 | 95  | 93 |
|        |             |                 | 7.0              | 105 | 104 | 103 | 101  | 104 | 103 | 102 | 101  | 102 | 101 | 100 | 99   | 100 | 99 | 98 | 97  | 95 |
|        |             |                 | 10.0             | 106 | 105 | 104 | 103  | 105 | 104 | 103 | 102  | 103 | 102 | 101 | 101  | 100 | 99 | 99 | 96  | 96 |

