

屋内照明器具特性

品番 (品名)	XND5 5 9 1 S N				
光源	LED5000_80_5765 x1 5765.0 lm				
管理番号	K0160727 (0) DB 1				
BZ分類	BZ2 / 0.9 / BZ1				

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%																			
下方光束	100%																			
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.76	0.6	6.9	6.0	5.4	5.0	6.8	6.0	5.4	5.0	6.7	5.9	5.4	5.0	6.5	5.8	5.3	5.0	4.8
	中	0.72	0.8	8.0	7.2	6.6	6.2	7.9	7.1	6.6	6.2	7.6	7.0	6.5	6.2	7.5	6.9	6.5	6.1	6.0
	否	0.64	1.0	8.6	7.9	7.4	7.0	8.5	7.8	7.3	7.0	8.2	7.7	7.3	6.9	8.1	7.6	7.2	6.9	6.7
			1.25	9.1	8.5	8.0	7.6	8.9	8.4	7.9	7.6	8.7	8.2	7.9	7.6	8.5	8.1	7.8	7.5	7.3
下方投影面積		cm ²	1.5	9.4	8.8	8.4	8.1	9.2	8.7	8.4	8.0	9.0	8.6	8.3	8.0	8.8	8.5	8.2	7.9	7.7
等価発光面積		cm ²	2.0	9.8	9.3	9.0	8.7	9.6	9.2	8.9	8.6	9.4	9.1	8.8	8.5	9.2	8.9	8.7	8.5	8.3
取付高さ	器具間隔最大限		2.5	10.0	9.6	9.3	9.1	9.9	9.5	9.2	9.0	9.6	9.4	9.1	8.9	9.4	9.2	9.0	8.8	8.6
	横方向 (A)	縦方向 (B)	3.0	10.1	9.8	9.5	9.3	10.0	9.7	9.5	9.3	9.8	9.5	9.3	9.1	9.6	9.4	9.2	9.0	8.8
Hm	1.34Hm	1.34Hm	4.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.5	9.7	9.6	9.5	9.3	9.1
			5.0	10.4	10.2	10.0	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.7	9.9	9.7	9.6	9.5	9.3
			7.0	10.5	10.4	10.3	10.1	10.4	10.3	10.2	10.1	10.2	10.1	10.0	9.9	10.0	9.9	9.8	9.7	9.5
			10.0	10.6	10.5	10.4	10.3	10.5	10.4	10.3	10.2	10.3	10.2	10.1	10.1	10.0	9.9	9.9	9.9	9.6

