

# 屋内照明器具特性

品番 (品名)	XND5580SN	
光源	LED5000_80_5665 ×1	5665.0lm
管理番号	K0160725(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	壁	照明率 ( X0.01 )																ZCM
下方光束	100%	床	照明率 ( X0.01 )																ZCM
保守率	良 中 否	0.76 0.72 0.64	室指数																
			0.6	83	77	73	71	83	77	73	70	81	76	73	70	80	76	72	70
0.8	90	84	81	78	89	84	80	78	87	83	80	78	86	82	79	77	76		
1.0	94	89	85	83	93	88	85	83	91	87	85	82	90	86	84	82	81		
1.25	97	93	89	87	96	92	89	87	94	91	88	86	93	90	88	86	84		
1.5	99	95	92	90	98	94	92	89	96	93	91	89	94	92	90	88	87		
2.0	101	98	96	94	100	97	95	93	98	96	94	92	97	95	93	92	90		
2.5	103	100	98	96	102	99	97	96	100	98	96	95	98	96	95	94	92		
3.0	104	102	100	98	103	101	99	97	101	99	98	96	99	97	96	95	93		
4.0	105	103	102	100	104	102	101	100	102	100	99	98	100	99	98	97	95		
5.0	106	104	103	102	105	103	102	101	102	101	100	100	100	100	99	98	96		
7.0	106	105	104	104	105	104	104	103	103	102	102	101	101	101	100	99	97		
10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98		

