

# 屋内照明器具特性

品番 (品名)	XND1011WW															
光源	LED4000_85_1030 x1 1030.0 1m															
管理番号	K0158782(0)DB1															
BZ分類	BZ2/0.9/BZ1/3.5/BZ2/8.5/BZ1															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 ( X0.01) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.81	0.6	70	61	55	51	69	61	55	51	67	60	55	51	66	59	54	51	49	
		0.77	0.8	80	72	66	62	79	71	66	62	77	70	65	62	75	69	65	62	60	
			1.0	86	79	73	70	85	78	73	69	82	77	72	69	80	75	72	69	67	
		0.68	1.25	90	84	80	76	89	83	79	76	87	82	78	75	85	81	77	75	73	
下方投影面積	c m <sup>2</sup>	1.5	93	88	84	80	92	87	83	80	90	86	82	79	88	84	81	79	77		
		2.0	97	93	89	86	96	92	89	86	94	90	87	85	92	89	86	84	82		
取付高さ	器具間隔最大限		2.5	100	96	93	90	98	95	92	90	96	93	91	89	94	92	89	88		
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	94	92	98	95	93	91	95	93	92	90		
H m	1.15 H m	1.15 H m	4.0	103	101	98	96	102	100	97	96	100	98	96	94	97	96	94	93		
			5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95		
			7.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97		
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	96		

