

# 屋内照明器具特性

品番 (品名)	SLB15784 + SLK22012 + SLK290	
光源	LLD3421LCB1 ×1	700.0 1m
管理番号	K0193691 (0) DB1	
BZ分類	BZ1/0.9 / BZ2/3.5 / BZ3	

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 8 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	84 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.63	0.6	0.6	66	58	53	49	64	57	53	49	62	56	52	49	60	55	51	48	46
	中 0.6	0.6	0.8	72	65	60	56	71	64	59	56	68	62	58	55	65	61	57	54	52
	否 0.56	0.6	1.0	77	70	65	61	75	69	64	61	72	67	63	60	69	65	61	59	56
下方投影面積	c m <sup>2</sup>	1.25	80	74	69	66	78	73	69	65	75	70	67	64	72	68	65	63	60	
		1.5	83	77	73	69	81	76	72	69	78	73	70	67	74	71	68	66	63	
等価発光面積	c m <sup>2</sup>	2.0	86	81	78	74	84	80	76	73	81	77	74	72	77	74	72	70	66	
		2.5	88	84	81	78	86	83	79	77	83	80	77	75	79	77	75	73	69	
取付高さ	器具間隔最大限		3.0	90	86	83	80	88	85	82	79	84	81	79	77	81	78	76	75	71
H m	横方向 (A)	縦方向 (B)	4.0	92	89	86	84	90	87	85	82	86	84	82	80	82	81	79	77	73
	0.46 H m	0.48 H m	5.0	93	90	88	86	91	89	87	85	87	85	83	82	83	82	81	79	75
			7.0	94	92	90	89	92	90	89	87	88	87	86	84	85	84	82	81	77
			10.0	95	94	92	91	93	92	91	89	89	88	87	86	86	85	84	83	79

