

屋内照明器具特性

品番 (品名)	SLB15784+SLK22013														
光源	LLD2401LCB1 ×1 500.0 lm														
管理番号	K0193966(0)DB1														
BZ分類	BZ1														

器具効率	79%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	79%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	57	50	45	42	56	49	45	42	55	49	45	42	53	48	45	42	41		
		0.8	64	58	54	51	63	58	54	51	62	57	54	51	60	56	53	51	50		
		1.0	69	64	60	57	68	63	60	57	66	62	59	57	65	61	58	56	55		
		1.25	72	68	64	62	71	67	64	62	70	66	63	61	68	65	63	61	60		
下方投影面積	c m ²	1.5	75	71	68	65	74	70	67	65	72	69	66	64	70	68	66	64	62		
		2.0	77	74	72	69	77	74	71	69	75	72	70	68	73	71	69	68	66		
取付高さ	器具間隔最大限		2.5	79	76	74	72	78	76	74	72	76	74	73	71	75	73	72	70	69	
	横方向 (A)	縦方向 (B)	3.0	80	78	76	74	79	77	75	74	78	76	74	73	76	74	73	72	70	
H m	1.32 H m	1.32 H m	4.0	82	80	78	77	81	79	78	76	79	78	76	75	77	76	75	74	72	
			5.0	82	81	80	78	81	80	79	78	80	79	78	77	78	77	76	75	74	
			7.0	83	82	81	80	82	81	80	80	81	80	79	78	79	78	77	75		
			10.0	84	83	82	82	83	82	82	81	81	81	80	80	80	79	79	78	76	

