

# 屋内照明器具特性

|         |                                              |  |  |  |  |
|---------|----------------------------------------------|--|--|--|--|
| 品番 (品名) | SLB15784+SLK22014+SLK290                     |  |  |  |  |
| 光源      | LLD2401LCB1 ×1                      500.0 lm |  |  |  |  |
| 管理番号    | K0193246(0)DB1                               |  |  |  |  |
| BZ分類    | BZ3/1.8/BZ4/6.0/BZ5                          |  |  |  |  |

|        |               |         |                  |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |     |
|--------|---------------|---------|------------------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率   | 82%           | 天井      | 80%              |      |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |     |
|        | 上方光束          |         | 16%              | 反射率  | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0%  |
|        | 下方光束          |         | 66%              |      | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |     |
| 室指数    | 照明率 ( X0.01 ) |         |                  |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    | ZCM |
| 保守率    | 良             | 0.63    | 0.6              | 50   | 41 | 36  | 32  | 48 | 40 | 35  | 31  | 45 | 38 | 34  | 30  | 42 | 36 | 32  | 29 | 27 |     |
|        | 中             | 0.6     | 0.8              | 57   | 48 | 43  | 39  | 55 | 47 | 42  | 38  | 51 | 45 | 40  | 37  | 47 | 42 | 38  | 36 | 33 |     |
|        | 否             | 0.56    | 1.0              | 61   | 54 | 48  | 44  | 59 | 52 | 47  | 43  | 55 | 49 | 45  | 42  | 51 | 46 | 43  | 40 | 37 |     |
|        |               |         | 0.56             | 1.25 | 65 | 58  | 53  | 49 | 63 | 57  | 52  | 48 | 58 | 53  | 49  | 46 | 54 | 50  | 47 | 44 | 40  |
| 下方投影面積 |               |         | c m <sup>2</sup> | 1.5  | 68 | 62  | 57  | 53 | 66 | 60  | 55  | 52 | 61 | 56  | 53  | 49 | 57 | 53  | 50 | 47 | 43  |
|        | 等価発光面積        |         | c m <sup>2</sup> | 2.0  | 72 | 66  | 62  | 59 | 69 | 64  | 60  | 57 | 64 | 60  | 57  | 54 | 60 | 57  | 54 | 52 | 47  |
| 取付高さ   | 器具間隔最大限       |         |                  | 2.5  | 74 | 70  | 66  | 62 | 72 | 67  | 64  | 61 | 67 | 63  | 60  | 58 | 62 | 59  | 57 | 55 | 50  |
|        | 横方向 (A)       | 縦方向 (B) |                  | 3.0  | 76 | 72  | 68  | 65 | 73 | 70  | 66  | 64 | 68 | 65  | 63  | 60 | 63 | 61  | 59 | 57 | 52  |
| H m    | 1.07H m       | 1.07H m |                  | 4.0  | 78 | 75  | 72  | 69 | 75 | 72  | 70  | 67 | 70 | 68  | 66  | 64 | 65 | 63  | 62 | 60 | 55  |
|        |               |         |                  | 5.0  | 79 | 77  | 74  | 72 | 77 | 74  | 72  | 70 | 72 | 70  | 68  | 66 | 67 | 65  | 64 | 62 | 56  |
|        |               |         |                  | 7.0  | 81 | 79  | 77  | 75 | 78 | 76  | 75  | 73 | 73 | 72  | 70  | 69 | 68 | 67  | 66 | 65 | 59  |
|        |               |         |                  | 10.0 | 82 | 81  | 79  | 78 | 80 | 78  | 77  | 75 | 74 | 73  | 72  | 71 | 69 | 68  | 68 | 67 | 60  |

