

屋内照明器具特性

品番 (品名)	XND9090SN		
光源	LED5000_80_10115 x1	10115.0 lm	
管理番号	K0160637(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	反射率	壁																
下方光束	100%		床	10%				10%				10%				10%			
		室指数	照明率 (X0.01)																ZCM
保守率	良 0.76	0.6	81	74	70	67	80	74	70	67	79	73	70	67	78	73	69	67	66
	中 0.72	0.8	88	82	78	75	87	81	78	75	85	81	77	74	84	80	77	74	73
	否 0.64	1.0	92	87	83	80	91	86	83	80	89	85	82	80	88	84	81	79	78
下方投影面積 等価発光面積	cm ² cm ²	1.25	95	91	87	85	94	90	87	84	93	89	86	84	91	88	85	83	82
		1.5	98	94	90	88	97	93	90	87	95	92	89	87	93	90	88	86	85
		2.0	100	97	94	92	99	96	94	92	97	95	93	91	95	93	92	90	88
取付高さ	器具間隔最大限		2.5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92
	横方向 (A)	縦方向 (B)	3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94
Hm	0.77Hm	0.77Hm	4.0	105	103	101	99	103	102	100	99	101	100	99	97	99	98	97	96
			5.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97
			7.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	96
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	101	101	100	97

