

屋内照明器具特性

品番 (品名)	XND9093SV									
光源	LED3500_80_10025 ×1					10025.0 1 m				
管理番号	K0160639 (0) DB 1									
BZ分類	BZ2/1.1/BZ1/4.5/BZ2/6.0/BZ1									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.76	0.6	70	60	55	50	69	60	54	50	67	59	54	50	65	58	54	50	49
		0.72	0.8	80	71	66	62	78	71	65	62	76	70	65	61	74	69	64	61	60
		0.64	1.0	86	78	73	69	84	78	73	69	82	76	72	69	80	75	71	68	67
			1.25	90	84	79	76	89	83	79	76	87	82	78	75	85	81	77	75	73
下方投影面積	c m ²	1.5	93	88	84	80	92	87	83	80	90	86	82	79	88	84	81	79	77	
		2.0	97	93	89	86	96	92	89	86	94	90	88	85	92	89	86	84	82	
取付高さ	器具間隔最大限		2.5	100	96	93	90	98	95	92	90	96	93	91	89	94	92	90	88	
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	95	92	98	95	93	91	96	93	92	90	
H m	1.20 H m	1.20 H m	4.0	103	101	98	96	102	100	98	96	100	98	96	94	97	96	94	93	
			5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95	93
			7.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	95	
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	96	

