

屋内照明器具特性	
品番 (品名)	SLB15785+SLK22002+SLK290
光源	LLD3411LCB1 ×1 700.0 lm
管理番号	K0193244 (0) DB 1
BZ分類	BZ1/0.7/BZ2/1.8/BZ3/8.5/BZ4

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.63 0.6 0.56	0.6	58	50	45	42	56	49	44	41	53	47	43	40	51	45	42	39	37
				0.8	64	57	52	48	62	56	51	48	59	53	49	46	56	51	48	45	42
				1.0	68	62	57	53	66	60	56	52	63	58	54	51	59	55	52	49	46
				1.25	72	66	61	58	70	64	60	57	66	61	58	55	62	58	55	53	49
下方投影面積		cm ²	1.5	75	69	65	61	72	67	63	60	68	64	61	58	64	61	58	56	52	
				2.0	78	73	69	66	76	71	68	65	71	68	65	62	67	64	62	60	56
取付高さ	器具間隔最大限			2.5	80	76	73	70	78	74	71	68	73	70	68	65	69	67	64	63	58
	横方向 (A)		縦方向 (B)		3.0	82	78	75	72	79	76	73	71	75	72	70	68	70	68	66	65
Hm	0.76Hm		0.76Hm	4.0	84	81	78	76	81	79	76	74	77	74	72	71	72	70	69	67	62
				5.0	85	83	80	78	83	80	78	76	78	76	74	73	73	72	70	69	64
				7.0	86	85	83	81	84	82	81	79	79	78	76	75	74	73	72	71	66
				10.0	88	86	85	84	85	84	83	81	80	79	78	77	76	75	74	73	67

