

屋内照明器具特性

品番 (品名)	XNG2560SWK (J YOUJI)	
光源	LED4000_85_2190 ×1 2190.0 lm	
管理番号	K0160267 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																				ZCM
保守率	良 0.81	0.6	86	81	77	75	86	81	77	75	84	80	77	75	83	79	77	75	74		
	中 0.77		0.8	92	87	83	81	91	86	83	81	89	86	83	81	88	85	82	80	79	
	否 0.68		1.0	95	91	88	85	94	90	87	85	93	89	87	85	91	88	86	84	83	
下方投影面積	cm ²	1.25	98	94	91	89	97	93	91	89	95	92	90	88	94	91	89	87	86		
		1.5	99	96	93	91	98	95	93	91	97	94	92	90	95	93	91	90	88		
等価発光面積	cm ²	2.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	93	91		
		2.5	103	101	99	97	102	100	98	97	100	98	97	95	98	97	96	94	93		
取付高さ	器具間隔最大限		3.0	104	102	100	99	103	101	99	98	101	99	98	97	99	98	97	94		
	横方向 (A)	縦方向 (B)	4.0	105	103	102	101	104	102	101	100	102	101	100	99	100	99	98	95		
Hm	0.82Hm	0.82Hm	5.0	106	104	103	102	105	103	102	101	102	102	101	100	101	100	99	96		
			7.0	106	105	105	104	105	104	104	103	103	102	102	101	101	101	100	97		
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	98		

