

# 屋内照明器具特性

|         |                               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XWG432AGNJ ( J YOUJ I )       |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_3040 x1 3040.0 1 m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0178169 ( 0 ) D 1            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                           |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |           |               |      |      |     |      |      |      |     |      |     |      |     |      |     |      |     |     |     |     |
|--------|------------------|-----------|---------------|------|------|-----|------|------|------|-----|------|-----|------|-----|------|-----|------|-----|-----|-----|-----|
| 器具効率   | 100 %            | 天井        | 80 %          |      |      |     | 70 % |      |      |     | 50 % |     |      |     | 30 % |     |      |     | 0 % |     |     |
|        |                  |           | 反射率           | 壁    | 70   | 50  | 30   | 10   | 70   | 50  | 30   | 10  | 70   | 50  | 30   | 10  | 70   | 50  | 30  | 10  | 0 % |
|        |                  |           |               | 床    | 10 % |     |      |      | 10 % |     |      |     | 10 % |     |      |     | 10 % |     |     |     | 0 % |
| 上方光束   | 6 %              | 室指数       | 照明率 ( X0.01 ) |      |      |     |      |      |      |     |      |     |      |     |      |     |      |     |     |     |     |
| 下方光束   | 94 %             |           | ZCM           |      |      |     |      |      |      |     |      |     |      |     |      |     |      |     |     |     |     |
| 保守率    | 良<br>中<br>否      | 0.83      | 0.6           | 5.5  | 4.2  | 3.5 | 2.9  | 5.3  | 4.2  | 3.4 | 2.9  | 5.0 | 4.0  | 3.3 | 2.8  | 4.8 | 3.9  | 3.2 | 2.8 | 2.6 |     |
|        |                  | 0.81      | 0.8           | 6.5  | 5.3  | 4.5 | 3.9  | 6.3  | 5.2  | 4.4 | 3.9  | 5.9 | 5.0  | 4.3 | 3.8  | 5.6 | 4.8  | 4.2 | 3.7 | 3.5 |     |
|        |                  | 0.77      | 1.0           | 7.1  | 6.0  | 5.2 | 4.6  | 6.9  | 5.9  | 5.1 | 4.6  | 6.5 | 5.6  | 5.0 | 4.5  | 6.2 | 5.4  | 4.9 | 4.4 | 4.1 |     |
|        |                  |           | 1.25          | 7.7  | 6.7  | 5.9 | 5.3  | 7.5  | 6.5  | 5.8 | 5.3  | 7.1 | 6.3  | 5.7 | 5.2  | 6.7 | 6.0  | 5.5 | 5.1 | 4.7 |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5       | 8.1           | 7.2  | 6.4  | 5.9 | 7.9  | 7.0  | 6.4  | 5.8 | 7.5  | 6.8 | 6.2  | 5.7 | 7.1  | 6.5 | 6.0  | 5.6 | 5.2 |     |     |
|        |                  | 2.0       | 8.7           | 7.9  | 7.2  | 6.7 | 8.4  | 7.7  | 7.1  | 6.6 | 8.0  | 7.4 | 6.9  | 6.5 | 7.6  | 7.1 | 6.7  | 6.3 | 6.0 |     |     |
| 取付高さ   | 器具間隔最大限          |           | 2.5           | 9.0  | 8.3  | 7.8 | 7.3  | 8.8  | 8.2  | 7.6 | 7.2  | 8.4 | 7.9  | 7.4 | 7.0  | 8.0 | 7.6  | 7.2 | 6.8 | 6.5 |     |
|        | 横方向 ( A )        | 縦方向 ( B ) | 3.0           | 9.3  | 8.7  | 8.2 | 7.7  | 9.1  | 8.5  | 8.0 | 7.6  | 8.6 | 8.2  | 7.8 | 7.4  | 8.3 | 7.9  | 7.5 | 7.2 | 6.8 |     |
| 1.5m   | 1.99 m           | 2.19 m    | 4.0           | 9.6  | 9.1  | 8.7 | 8.3  | 9.4  | 8.9  | 8.5 | 8.2  | 9.0 | 8.6  | 8.3 | 8.0  | 8.6 | 8.3  | 8.0 | 7.7 | 7.3 |     |
| 2      | 2.62             | 2.72      | 5.0           | 9.8  | 9.4  | 9.0 | 8.7  | 9.6  | 9.2  | 8.9 | 8.6  | 9.2 | 8.9  | 8.6 | 8.3  | 8.8 | 8.6  | 8.3 | 8.1 | 7.7 |     |
| 2.5    | 3.25             | 3.28      | 7.0           | 10.0 | 9.7  | 9.4 | 9.2  | 9.8  | 9.5  | 9.3 | 9.0  | 9.4 | 9.2  | 9.0 | 8.8  | 9.1 | 8.9  | 8.7 | 8.5 | 8.1 |     |
| 3      | 3.88             | 3.85      | 10.0          | 10.2 | 10.0 | 9.8 | 9.6  | 10.0 | 9.8  | 9.6 | 9.4  | 9.6 | 9.5  | 9.3 | 9.1  | 9.3 | 9.1  | 9.0 | 8.9 | 8.4 |     |

