

屋内照明器具特性

品番 (品名)	YYY21263K+YYY29912									
光源	LED3000_70_890 x1					890.0 l m				
管理番号	K0186979 (1) DR 1									
BZ分類	BZ4/1.1/BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	9 %	室指数	照明率 (X0.01)																ZCM	
下方光束	91 %																			
保守率	良 中 否	0.67	0.6	57	46	38	33	56	45	38	33	52	43	37	32	50	41	36	32	29
		0.63	0.8	67	56	48	42	65	54	47	42	61	52	46	41	58	50	45	40	37
			1.0	73	62	55	49	71	61	54	49	67	58	52	48	63	56	51	47	43
		0.56	1.25	78	69	62	56	76	67	61	55	72	64	59	54	68	62	57	53	49
下方投影面積	c m ²	1.5	82	73	67	61	80	72	65	60	75	69	63	59	71	66	61	57	54	
		2.0	87	80	74	69	85	78	73	68	80	75	70	66	76	72	68	64	60	
取付高さ	器具間隔最大限		2.5	91	84	79	74	88	82	77	73	84	79	75	71	79	75	72	69	64
	横方向 (A)	縦方向 (B)	3.0	93	87	82	78	91	85	81	77	86	82	78	75	82	78	75	72	68
1.5m	1.56 m	2.18 m	4.0	96	91	87	84	94	89	86	82	89	86	82	80	85	82	79	77	72
2	2.06	2.76	5.0	98	94	90	87	96	92	89	86	91	88	85	83	87	84	82	80	75
2.5	2.57	3.36	7.0	100	97	94	92	98	95	93	90	93	91	89	87	89	87	86	84	79
3	3.07	3.98	10.0	102	100	97	95	99	97	96	94	95	93	92	90	91	90	88	87	82

