

屋内照明器具特性	
品番 (品名)	NTS72731S+NTS90101
光源	LED4000_70_505 ×1 505.0 l m
管理番号	K0155954 (*) DJ 1
B Z 分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM	
下方光束		100 %																						
保守率		良 中 否	0.6	88	83	80	77	87	83	79	77	86	82	79	77	85	81	79	77	76				
			0.8	93	89	86	83	93	88	85	83	91	88	85	83	90	87	84	83	82				
			1.0	96	92	89	87	96	92	89	87	94	91	89	87	93	90	88	86	85				
			0.56	1.25	99	95	93	91	98	95	92	90	97	94	92	90	95	93	91	89	88			
下方投影面積		cm ²	1.5	101	97	95	93	100	97	95	93	98	96	94	92	96	94	93	91	90				
			等価発光面積		cm ²	2.0	103	100	98	96	102	99	97	96	100	98	96	95	98	97	95	94	92	
取付 高さ	器具間隔最大限		2.5	104		102	100	98	103	101	99	98	101	99	98	97	99	98	97	96	94			
	横方向 (A)		縦方向 (B)		3.0	105	103	101	100	104	102	101	99	102	100	99	98	100	99	98	97	95		
Hm	0.48Hm		0.48Hm		4.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	99	98	96		
					5.0	106	105	104	103	105	104	103	102	103	102	101	101	101	100	99	97			
					7.0	107	106	105	105	106	105	104	104	104	103	103	102	101	101	100	98			
					10.0	108	107	106	106	106	105	105	104	104	103	103	102	101	101	100	98			