

# 屋内照明器具特性

|         |                                    |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XWG452AGNJ ( J YOUJ I )            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_4940 x1      4940.0 1 m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0178169 ( 0 ) D 1                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                                |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |         |                 |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
|--------|---------|-----------------|------|------|------|-----|------|------|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率   | 100 %   | 天井              | 80 % |      |      |     | 70 % |      |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|        |         | 壁               | 70   | 50   | 30   | 10  | 70   | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
|        |         | 床               | 10 % |      |      |     | 10 % |      |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 上方光束   | 6 %     | 室指数             |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
| 下方光束   | 94 %    | 照明率 ( X0.01 )   |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
|        |         | ZCM             |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
| 保守率    | 良       | 0.83            | 0.6  | 5.5  | 4.2  | 3.5 | 2.9  | 5.3  | 4.2 | 3.4 | 2.9  | 5.0 | 4.0 | 3.3 | 2.8  | 4.8 | 3.9 | 3.2 | 2.8 | 2.6 |
|        | 中       | 0.81            | 0.8  | 6.5  | 5.3  | 4.5 | 3.9  | 6.3  | 5.2 | 4.4 | 3.9  | 5.9 | 5.0 | 4.3 | 3.8  | 5.6 | 4.8 | 4.2 | 3.7 | 3.5 |
|        | 否       | 0.77            | 1.0  | 7.1  | 6.0  | 5.2 | 4.6  | 6.9  | 5.9 | 5.1 | 4.6  | 6.5 | 5.6 | 5.0 | 4.5  | 6.2 | 5.4 | 4.9 | 4.4 | 4.1 |
|        |         |                 | 1.25 | 7.7  | 6.7  | 5.9 | 5.3  | 7.5  | 6.5 | 5.8 | 5.3  | 7.1 | 6.3 | 5.7 | 5.2  | 6.7 | 6.0 | 5.5 | 5.1 | 4.7 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5  | 8.1  | 7.2  | 6.4 | 5.9  | 7.9  | 7.0 | 6.4 | 5.8  | 7.5 | 6.8 | 6.2 | 5.7  | 7.1 | 6.5 | 6.0 | 5.6 | 5.2 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0  | 8.7  | 7.9  | 7.2 | 6.7  | 8.4  | 7.7 | 7.1 | 6.6  | 8.0 | 7.4 | 6.9 | 6.5  | 7.6 | 7.1 | 6.7 | 6.3 | 6.0 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5  | 9.0  | 8.3  | 7.8 | 7.3  | 8.8  | 8.2 | 7.6 | 7.2  | 8.4 | 7.9 | 7.4 | 7.0  | 8.0 | 7.6 | 7.2 | 6.8 | 6.5 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0  | 9.3  | 8.7  | 8.2 | 7.7  | 9.1  | 8.5 | 8.0 | 7.6  | 8.6 | 8.2 | 7.8 | 7.4  | 8.3 | 7.9 | 7.5 | 7.2 | 6.8 |
| 1.5m   | 1.99 m  | 2.19 m          | 4.0  | 9.6  | 9.1  | 8.7 | 8.3  | 9.4  | 8.9 | 8.5 | 8.2  | 9.0 | 8.6 | 8.3 | 8.0  | 8.6 | 8.3 | 8.0 | 7.7 | 7.3 |
| 2      | 2.62    | 2.72            | 5.0  | 9.8  | 9.4  | 9.0 | 8.7  | 9.6  | 9.2 | 8.9 | 8.6  | 9.2 | 8.9 | 8.6 | 8.3  | 8.8 | 8.6 | 8.3 | 8.1 | 7.7 |
| 2.5    | 3.25    | 3.28            | 7.0  | 10.0 | 9.7  | 9.4 | 9.2  | 9.8  | 9.5 | 9.3 | 9.0  | 9.4 | 9.2 | 9.0 | 8.8  | 9.1 | 8.9 | 8.7 | 8.5 | 8.1 |
| 3      | 3.88    | 3.85            | 10.0 | 10.2 | 10.0 | 9.8 | 9.6  | 10.0 | 9.8 | 9.6 | 9.4  | 9.6 | 9.5 | 9.3 | 9.1  | 9.3 | 9.1 | 9.0 | 8.9 | 8.4 |

