

屋内照明器具特性

| | | |
|---------|--------------------------|----------|
| 品番 (品名) | SLB16781+SLK22008+SLK290 | |
| 光源 | LLD2421LCB1 ×1 | 500.0 1m |
| 管理番号 | K0192486(1)DR1 | |
| BZ分類 | BZ1 | |

| 器具効率 | 57% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
|--------|---------|-----------------|----------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | | |
| 上方光束 | 0% | 壁 | | | | | | | | | | | | | | | | | | |
| 下方光束 | 57% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| | | 室指数 | 照明率 (X 0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 51 | 49 | 47 | 46 | 51 | 49 | 47 | 46 | 50 | 48 | 47 | 46 | 50 | 48 | 47 | 46 | 45 |
| | 中 | 0.63 | 0.8 | 54 | 52 | 50 | 49 | 54 | 51 | 50 | 49 | 53 | 51 | 50 | 49 | 52 | 51 | 49 | 49 | 48 |
| | 否 | 0.56 | 1.0 | 56 | 54 | 52 | 51 | 55 | 53 | 52 | 51 | 54 | 53 | 52 | 51 | 54 | 52 | 51 | 50 | 50 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 57 | 55 | 54 | 53 | 57 | 55 | 54 | 53 | 56 | 54 | 53 | 52 | 55 | 54 | 53 | 52 | 51 |
| | | | 1.5 | 58 | 56 | 55 | 54 | 57 | 56 | 55 | 54 | 56 | 55 | 54 | 53 | 56 | 55 | 54 | 53 | 52 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 59 | 58 | 57 | 56 | 58 | 57 | 56 | 55 | 57 | 56 | 55 | 56 | 56 | 55 | 54 | 53 | |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 60 | 58 | 58 | 57 | 59 | 58 | 57 | 56 | 58 | 57 | 56 | 56 | 57 | 56 | 55 | 54 | |
| Hm | 0.34Hm | 0.35Hm | 3.0 | 60 | 59 | 58 | 58 | 59 | 59 | 58 | 57 | 58 | 58 | 57 | 57 | 57 | 57 | 56 | 55 | |
| | | | 4.0 | 61 | 60 | 59 | 59 | 60 | 59 | 59 | 58 | 59 | 58 | 58 | 57 | 58 | 57 | 57 | 57 | 55 |
| | | | 5.0 | 61 | 60 | 60 | 59 | 60 | 60 | 59 | 59 | 59 | 59 | 58 | 58 | 58 | 58 | 57 | 56 | |
| | | | 7.0 | 61 | 61 | 60 | 60 | 61 | 60 | 60 | 60 | 59 | 59 | 59 | 59 | 58 | 58 | 58 | 56 | |
| | | | 10.0 | 62 | 61 | 61 | 61 | 61 | 61 | 60 | 60 | 60 | 59 | 59 | 59 | 59 | 58 | 58 | 57 | |

