

屋内照明器具特性

品番 (品名)	SLB16781+SLK22009+SLK290									
光源	LLD3411LCB1 ×1 700.0 1 m									
管理番号	K0193244 (0) DB 1									
BZ分類	BZ1 / 0.7 / BZ2 / 1.8 / BZ3 / 8.5 / BZ4									

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	14 %																			
下方光束	72 %																			
室指数	照明率 (X0.01)																ZCM			
保守率	良 中 否 0.63 0.6 0.56	0.6	58	50	45	42	56	49	44	41	53	47	43	40	51	45	42	39	37	
		0.8	64	57	52	48	62	56	51	48	59	53	49	46	56	51	48	45	42	
		1.0	68	62	57	53	66	60	56	52	63	58	54	51	59	55	52	49	46	
		1.25	72	66	61	58	70	64	60	57	66	61	58	55	62	58	55	53	49	
下方投影面積	c m ²	1.5	75	69	65	61	72	67	63	60	68	64	61	58	64	61	58	56	52	
		2.0	78	73	69	66	76	71	68	65	71	68	65	62	67	64	62	60	56	
取付高さ	器具間隔最大限		2.5	80	76	73	70	78	74	71	68	73	70	68	65	69	67	64	63	58
	横方向 (A)	縦方向 (B)	3.0	82	78	75	72	79	76	73	71	75	72	70	68	70	68	66	65	60
H m	0.76 H m	0.76 H m	4.0	84	81	78	76	81	79	76	74	77	74	72	71	72	70	69	67	62
			5.0	85	83	80	78	83	80	78	76	78	76	74	73	73	72	70	69	64
			7.0	86	85	83	81	84	82	81	79	79	78	76	75	74	73	72	71	66
			10.0	88	86	85	84	85	84	83	81	80	79	78	77	76	75	74	73	67

