

# 屋内照明器具特性

|         |                          |          |
|---------|--------------------------|----------|
| 品番 (品名) | SLB16780+SLK22009+SLK290 |          |
| 光源      | LLD3401LCB1 ×1           | 700.0 lm |
| 管理番号    | K0192481(1)DR1           |          |
| BZ分類    | BZ1                      |          |

|        |                 |         |                 |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |    |  |     |
|--------|-----------------|---------|-----------------|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|----|--|-----|
| 器具効率   | 38%             | 天井      | 80%             |     |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |    |  |     |
|        |                 | 壁       | 70              | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |    |  |     |
| 上方光束   | 0%              | 床       | 10%             |     |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0% |    |    |  |     |
| 下方光束   | 38%             | 室指数     | 照明率 (X0.01)     |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |    |  | ZCM |
| 保守率    | 良               | 0.67    | 0.6             | 31  | 29 | 27 | 26  | 31 | 29 | 27 | 26  | 30 | 28 | 27 | 26  | 30 | 28 | 27 | 26 | 26 |    |  |     |
|        | 中               | 0.63    | 0.8             | 34  | 32 | 30 | 29  | 34 | 32 | 30 | 29  | 33 | 31 | 30 | 29  | 32 | 31 | 30 | 29 | 28 |    |  |     |
|        | 否               | 0.56    | 1.0             | 35  | 34 | 32 | 31  | 35 | 33 | 32 | 31  | 34 | 33 | 32 | 31  | 34 | 33 | 32 | 31 | 30 |    |  |     |
|        |                 |         | 1.25            | 37  | 35 | 34 | 33  | 36 | 35 | 34 | 33  | 36 | 34 | 33 | 32  | 35 | 34 | 33 | 32 | 32 |    |  |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5             | 37  | 36 | 35 | 34  | 37 | 36 | 35 | 34  | 36 | 35 | 34 | 34  | 36 | 35 | 34 | 33 | 33 |    |  |     |
|        | 等価発光面積          |         | cm <sup>2</sup> | 2.0 | 38 | 37 | 36  | 35 | 38 | 37 | 36  | 35 | 37 | 36 | 36  | 35 | 37 | 36 | 35 | 35 | 34 |  |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 39  | 38 | 37 | 36  | 39 | 38 | 37 | 36  | 38 | 37 | 36 | 36  | 37 | 36 | 36 | 35 | 35 |    |  |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 39  | 38 | 38 | 37  | 39 | 38 | 37 | 37  | 38 | 38 | 37 | 36  | 37 | 37 | 36 | 36 | 35 |    |  |     |
| Hm     | 0.87Hm          | 0.86Hm  | 4.0             | 40  | 39 | 39 | 38  | 39 | 39 | 38 | 38  | 39 | 38 | 38 | 37  | 38 | 37 | 37 | 37 | 36 |    |  |     |
|        |                 |         | 5.0             | 40  | 40 | 39 | 39  | 40 | 39 | 39 | 38  | 39 | 38 | 38 | 38  | 38 | 38 | 37 | 37 | 36 |    |  |     |
|        |                 |         | 7.0             | 40  | 40 | 40 | 39  | 40 | 40 | 39 | 39  | 39 | 39 | 39 | 39  | 38 | 38 | 38 | 38 | 37 |    |  |     |
|        |                 |         | 10.0            | 41  | 40 | 40 | 40  | 40 | 40 | 40 | 40  | 39 | 39 | 39 | 39  | 39 | 38 | 38 | 38 | 37 |    |  |     |

