

屋内照明器具特性

品番 (品名)	SLB16780+SLK22011	
光源	LLD2411LCB1 ×1	500.0 1m
管理番号	K0192999(0)DB1	
BZ分類	BZ1	

器具効率	99%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	99%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	91	86	83	82	90	86	83	81	89	85	83	81	88	85	83	81	80	
	中 0.63		0.8	95	91	88	86	94	91	88	86	93	90	88	86	92	89	87	86	85
	否 0.56		1.0	97	94	91	90	97	93	91	89	95	93	91	89	94	92	90	89	88
下方投影面積	cm ²	1.25	99	96	94	92	99	96	94	92	97	95	93	92	96	94	92	91	90	
		1.5	101	98	96	94	100	97	96	94	98	96	95	93	97	95	94	93	91	
等価発光面積	cm ²	2.0	102	100	98	97	102	100	98	97	100	98	97	96	98	97	96	95	93	
		2.5	104	102	100	99	103	101	99	98	101	99	98	97	99	98	97	96	94	
取付高さ	器具間隔最大限		3.0	104	103	101	100	103	102	100	99	101	100	99	98	100	99	98	95	
	横方向 (A)	縦方向 (B)	4.0	105	104	103	102	104	103	102	101	102	101	100	100	100	99	98	96	
Hm	0.78Hm	0.78Hm	5.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	97	
			7.0	106	105	105	104	105	104	104	103	103	103	102	102	101	101	100	97	
			10.0	107	106	106	105	106	105	105	104	103	103	103	102	101	101	101	98	

