

屋内照明器具特性	
品番 (品名)	NYM20223+NYK00118
光源	LED5000_85_21750 ×1 21750.0 lm
管理番号	K0185728 (0) DB1
BZ分類	BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		6 %	室指数	照明率 (X0.01)																		Z CM	
下方光束		94 %																					
保守率		良 中 否	0.77	0.6	65	55	48	44	64	54	48	44	61	53	47	43	59	51	46	43	41		
			0.72	0.8	74	65	58	54	72	64	58	53	69	62	57	53	67	60	56	52	50		
			0.68	1.0	80	71	65	60	78	70	64	60	75	68	63	59	72	66	62	58	56		
				1.25	85	77	71	67	83	76	70	66	79	73	69	65	76	71	67	64	61		
下方投影面積		cm ²	1.5	88	81	76	71	86	80	75	71	83	77	73	69	79	75	71	68	65			
等価発光面積			cm ²	2.0	92	87	82	78	90	85	81	77	87	82	79	76	83	80	77	74	71		
取付 高さ	器具間隔最大限		2.5	95	90	86	82	93	89	85	81	90	86	83	80	86	83	80	78	74			
	横方向 (A)		縦方向 (B)	3.0	97	93	89	86	95	91	88	85	91	88	85	83	88	85	83	81	77		
H m	1.11 H m	1.11 H m	4.0	99	96	93	90	97	94	92	89	94	91	89	87	90	88	86	85	81			
			5.0	101	98	95	93	99	96	94	92	95	93	91	89	92	90	88	87	83			
			7.0	103	100	98	97	101	99	97	95	97	95	94	93	94	92	91	90	86			
			10.0	104	102	101	99	102	101	99	98	98	97	96	95	95	94	93	92	88			

