

屋内照明器具特性	
品番 (品名)	NYM20224+NYK00117
光源	LED5000_85_30240 ×1 30240.0 lm
管理番号	K0185714 (0) DB1
BZ分類	BZ3

器具効率		100 % 上方光束 2 % 下方光束 98 %		反射率	天井	80 %				70 %				50 %				30 %				0 %		
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
					床	10 %				10 %				10 %				10 %				0 %		
					室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.83	0.6	65	55	48	44	64	54	48	44	62	53	48	44	60	52	47	43	41			
			0.81	0.8	75	65	59	54	73	65	59	54	71	63	58	54	68	62	57	53	51			
			0.77	1.0	81	72	66	62	79	71	66	61	77	70	65	61	74	68	64	60	58			
				1.25	86	78	73	68	84	77	72	68	81	76	71	67	79	74	70	66	64			
下方投影面積 等価発光面積		cm ² cm ²		1.5	89	82	77	73	88	81	77	73	85	79	75	72	82	78	74	71	68			
				2.0	94	88	84	80	92	87	83	79	89	85	81	78	86	83	80	77	74			
				2.5	96	92	88	84	95	91	87	84	92	88	85	82	89	86	83	81	78			
				3.0	98	94	91	88	97	93	90	87	94	91	88	85	91	88	86	84	81			
取付 高さ	器具間隔最大限			4.0	101	97	95	92	99	96	93	91	96	94	91	89	93	91	89	88	85			
	横方向 (A)		縦方向 (B)			5.0	102	99	97	95	101	98	96	94	98	96	94	92	95	93	92	90	87	
						7.0	104	102	100	98	102	100	99	97	99	98	96	95	97	95	94	93	90	
	H m		1.24 H m		1.24 H m			10.0	105	103	102	101	103	102	101	100	101	99	98	97	98	97	96	95

