

屋内照明器具特性	
品番 (品名)	NYM2 0 1 2 1 Z + NYK0 0 1 0 6
光源	LED5 0 0 0 _ 8 5 _ 1 4 7 0 0 ×1 1 4 7 0 0 . 0 1 m
管理番号	K0 1 7 4 9 5 8 (0) D 1
B Z 分類	B Z 3 / 0 . 7 / B Z 2 / 1 . 8 / B Z 3 / 8 . 5 / B Z 2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		9 9 %																				
保守率		良 中 否	0 . 8 3	0 . 6	6 6	5 6	4 9	4 5	6 5	5 5	4 9	4 5	6 3	5 4	4 9	4 5	6 1	5 3	4 8	4 4	4 3	
			0 . 8 1	0 . 8	7 6	6 6	6 0	5 6	7 4	6 6	6 0	5 5	7 2	6 4	5 9	5 5	7 0	6 3	5 9	5 5	5 3	
			0 . 7 7	1 . 0	8 2	7 3	6 7	6 3	8 0	7 3	6 7	6 3	7 8	7 1	6 6	6 2	7 6	7 0	6 5	6 2	6 0	
				1 . 2 5	8 7	7 9	7 4	7 0	8 5	7 9	7 3	6 9	8 3	7 7	7 2	6 9	8 0	7 5	7 2	6 8	6 6	
下方投影面積		cm ²	1 . 5	9 0	8 4	7 9	7 4	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 3	8 4	7 9	7 6	7 3	7 1		
等価発光面積		cm ²	2 . 0	9 5	8 9	8 5	8 1	9 3	8 8	8 4	8 1	9 1	8 6	8 3	8 0	8 8	8 5	8 2	7 9	7 7		
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1		
	横方向 (A) 縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 3		
H m	1 . 0 7 H m	1 . 0 7 H m	4 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7		
			5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 6	9 5	9 3	9 2	8 9		
			7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2		
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	9 9	9 8	9 8	9 7	9 4		

