

屋内照明器具特性	
品番 (品名)	NYM2 0 1 2 1 Z + NYK0 0 1 0 8
光源	LED5 0 0 0 _ 8 5 _ 1 3 4 0 0 ×1 1 3 4 0 0 . 0 1 m
管理番号	K0 1 7 4 9 5 9 (0) D 1
BZ分類	BZ3 / 0 . 7 / BZ2 / 1 . 8 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		9 9 %																					
保守率		良 中 否	0 . 7 7	0 . 6	6 6	5 5	4 9	4 4	6 4	5 5	4 9	4 4	6 2	5 4	4 8	4 4	6 0	5 3	4 8	4 4	4 2		
			0 . 7 2	0 . 8	7 5	6 6	6 0	5 5	7 4	6 5	5 9	5 5	7 1	6 4	5 9	5 4	6 9	6 3	5 8	5 4	5 2		
			0 . 6 8	1 . 0	8 1	7 3	6 7	6 2	8 0	7 2	6 6	6 2	7 7	7 0	6 5	6 2	7 5	6 9	6 5	6 1	5 9		
				1 . 2 5	8 6	7 9	7 3	6 9	8 5	7 8	7 3	6 9	8 2	7 6	7 2	6 8	8 0	7 5	7 1	6 7	6 5		
下方投影面積		cm ²	1 . 5	9 0	8 3	7 8	7 4	8 8	8 2	7 7	7 3	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 2	7 0			
等価発光面積		cm ²	2 . 0	9 4	8 9	8 4	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 7	8 4	8 1	7 8	7 6			
取付 高さ	器具間隔最大限		2 . 5	9 7	9 2	8 8	8 5	9 5	9 1	8 8	8 5	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	8 0			
	横方向 (A)		縦方向 (B)	3 . 0	9 9	9 5	9 1	8 8	9 7	9 4	9 0	8 8	9 5	9 1	8 9	8 6	9 2	8 9	8 7	8 5	8 2		
H m	1 . 0 6 H m	1 . 0 6 H m	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 4	9 2	9 0	9 4	9 2	9 1	8 9	8 6			
			5 . 0	1 0 2	1 0 0	9 8	9 5	1 0 1	9 9	9 7	9 5	9 8	9 6	9 5	9 3	9 6	9 4	9 3	9 1	8 8			
			7 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 8	9 7	9 6	9 7	9 6	9 5	9 4	9 1			
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3			

