

屋内照明器具特性	
品番 (品名)	NYM2 0 1 2 6 Z
光源	LED5000_85_51000 ×1 51000.0 lm
管理番号	K0174278 (2) DR 1
B Z 分類	BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1) Z C M																			
下方光束		9 9 %																					
保守率		良 中 否	0 . 6	6 4	5 4	4 7	4 2	6 3	5 3	4 7	4 2	6 1	5 2	4 6	4 2	5 9	5 1	4 6	4 2	4 0			
			0 . 8	7 4	6 4	5 7	5 3	7 2	6 3	5 7	5 3	7 0	6 2	5 6	5 2	6 8	6 1	5 6	5 2	5 0			
			1 . 0	8 0	7 1	6 5	6 0	7 8	7 0	6 4	6 0	7 6	6 9	6 3	5 9	7 3	6 7	6 3	5 9	5 7			
			0 . 7 7																				
下方投影面積 等価発光面積		c m ²	1 . 2 5	8 5	7 7	7 1	6 7	8 4	7 6	7 1	6 6	8 1	7 5	7 0	6 6	7 8	7 3	6 9	6 5	6 3			
			1 . 5	8 9	8 1	7 6	7 1	8 7	8 0	7 5	7 1	8 4	7 9	7 4	7 0	8 2	7 7	7 3	7 0	6 7			
			2 . 0	9 3	8 7	8 2	7 8	9 2	8 6	8 2	7 8	8 9	8 4	8 0	7 7	8 6	8 2	7 9	7 6	7 4			
取付 高さ	器具間隔最大限		2 . 5	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 3	9 2	8 8	8 4	8 2	8 9	8 6	8 3	8 0	7 8			
	横方向 (A)	縦方向 (B)	3 . 0	9 8	9 4	9 0	8 7	9 7	9 3	8 9	8 6	9 4	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 1			
H m	1 . 0 7 H m	1 . 0 7 H m	4 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 8	8 5			
			5 . 0	1 0 2	9 9	9 7	9 4	1 0 1	9 8	9 6	9 3	9 8	9 6	9 4	9 2	9 5	9 3	9 2	9 0	8 7			
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 0			
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3			

