

屋内照明器具特性

品番 (品名)	SLC50121														
光源	LED6200_70_4500 x1 4500.0 lm														
管理番号	K0194866(0)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	4%	反射率	床	10%				10%				10%				10%				0%
下方光束	96%		室指数	照明率 (X0.01) ZCM																
保守率	良 0.63 中 0.6 否 0.56	0.6	58	46	39	33	56	45	38	33	54	44	37	33	51	43	37	32	30	
		0.8	68	58	50	45	67	57	50	44	64	55	49	44	61	53	48	43	41	
		1.0	75	65	58	53	73	64	57	52	70	62	56	52	67	60	55	51	48	
		1.25	81	72	65	60	79	71	65	60	76	69	63	59	73	67	62	58	55	
下方投影面積	c m ²	1.5	85	77	71	65	83	76	70	65	80	73	68	64	76	71	67	63	60	
		2.0	90	83	78	73	88	82	77	73	85	80	75	71	82	77	73	70	67	
取付高さ	器具間隔最大限		2.5	93	88	83	79	92	86	82	78	88	84	80	76	85	81	78	75	
	横方向 (A)	縦方向 (B)	3.0	96	91	86	82	94	89	85	82	90	86	83	80	87	84	81	78	
H m	1.66 H m	1.66 H m	4.0	98	94	91	88	97	93	90	87	93	90	87	85	90	87	85	83	
			5.0	100	97	94	91	98	95	93	90	95	92	90	88	92	90	88	86	
			7.0	102	100	97	95	100	98	96	94	97	95	93	92	94	92	91	89	
			10.0	104	102	100	98	102	100	99	97	99	97	96	95	96	94	93	92	

