

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | XYM2011K                       |
| 光源       | LED5000_85_16000 ×1 16000.0 1m |
| 管理番号     | K0160686(0)DR1                 |
| BZ分類     | BZ5/0.7/BZ4                    |

|        |                 |         |                 |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    |     |    |
|--------|-----------------|---------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%            | 天井      | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |    |    |    | 0%  |    |
|        |                 | 壁       | 70              | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%              | 床       | 10%             |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%            | 室指数     | 照明率 ( X0.01)    |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    | ZCM |    |
| 保守率    | 良               | 0.83    | 0.6             | 58  | 46  | 39  | 34  | 57  | 46  | 39  | 33  | 55  | 45  | 38 | 33  | 53 | 44 | 38 | 33  | 31 |
|        | 中               | 0.81    | 0.8             | 69  | 58  | 50  | 45  | 67  | 57  | 50  | 45  | 65  | 56  | 49 | 45  | 62 | 55 | 49 | 44  | 42 |
|        | 否               | 0.77    | 1.0             | 76  | 66  | 58  | 53  | 74  | 65  | 58  | 53  | 71  | 63  | 57 | 53  | 69 | 62 | 56 | 52  | 50 |
|        |                 |         | 1.25            | 82  | 73  | 66  | 61  | 80  | 72  | 66  | 61  | 77  | 70  | 65 | 60  | 75 | 69 | 64 | 60  | 58 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5             | 86  | 78  | 72  | 67  | 84  | 77  | 71  | 66  | 82  | 75  | 70 | 66  | 79 | 73 | 69 | 65  | 63 |
|        | 等価発光面積          |         | cm <sup>2</sup> | 2.0 | 91  | 85  | 79  | 75  | 90  | 84  | 79  | 75  | 87  | 82 | 78  | 74 | 84 | 80 | 76  | 73 |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 95  | 89  | 85  | 81  | 93  | 88  | 84  | 80  | 90  | 86  | 82 | 79  | 88 | 84 | 81 | 78  | 76 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 97  | 92  | 88  | 85  | 96  | 91  | 87  | 84  | 93  | 89  | 86 | 83  | 90 | 87 | 84 | 82  | 79 |
| Hm     | 1.31Hm          | 1.30Hm  | 4.0             | 100 | 96  | 93  | 90  | 99  | 95  | 92  | 89  | 96  | 93  | 90 | 88  | 93 | 91 | 89 | 87  | 84 |
|        |                 |         | 5.0             | 102 | 99  | 96  | 93  | 100 | 97  | 95  | 92  | 98  | 95  | 93 | 91  | 95 | 93 | 91 | 90  | 87 |
|        |                 |         | 7.0             | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96 | 95  | 97 | 96 | 94 | 93  | 90 |
|        |                 |         | 10.0            | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99  | 101 | 100 | 99 | 98  | 99 | 98 | 97 | 96  | 93 |

