

屋内照明器具特性

品番 (品名)	NNN71500														
光源	NNU240105KLE9 x1 2050.0 1m														
管理番号	K0190783(0)DB1														
BZ分類	BZ2														

器具効率	91%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	91%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.81	0.6	62	53	47	43	61	52	47	43	59	51	46	43	57	51	46	43	41
	中	0.77	0.8	71	63	57	53	69	62	57	53	67	61	56	53	66	60	56	53	51
	否	0.68	1.0	76	69	64	60	75	68	64	60	73	67	63	60	71	66	62	59	58
			1.25	81	74	70	66	79	74	69	66	77	72	69	65	75	71	68	65	63
下方投影面積			1.5	83	78	74	70	82	77	73	70	80	76	72	69	78	74	71	69	67
			2.0	87	83	79	76	86	82	79	76	84	80	77	75	82	79	76	74	72
取付高さ	器具間隔最大限		2.5	90	86	83	80	88	85	82	79	86	83	81	78	84	82	79	78	76
	横方向 (A)	縦方向 (B)	3.0	91	88	85	83	90	87	84	82	88	85	83	81	86	84	82	80	78
Hm	1.17Hm	1.17Hm	4.0	93	90	88	86	92	89	87	85	90	88	86	84	88	86	84	83	81
			5.0	94	92	90	88	93	91	89	88	91	89	88	86	89	87	86	85	83
			7.0	95	94	92	91	94	93	92	90	92	91	90	89	90	89	88	87	85
			10.0	96	95	94	93	95	94	93	92	93	92	91	91	91	90	90	89	87

