

# 屋内照明器具特性

品番 (品名)	NNN71500															
光源	NNU140105KLE9 x1 1130.0 lm															
管理番号	K0190791(0)DB1															
BZ分類	BZ2															

器具効率	91%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 ( X0.01)																ZCM	
下方光束	91%																			
保守率	良 中 否 0.81 0.77 0.68	0.6	61	52	47	43	60	52	47	43	59	51	46	43	57	50	46	42	41	
		0.8	70	62	57	53	69	62	57	53	67	61	56	53	66	60	56	53	51	
		1.0	76	69	64	60	75	68	63	60	73	67	63	59	71	66	62	59	58	
		1.25	81	74	70	66	79	74	69	66	77	72	68	65	75	71	68	65	63	
下方投影面積	c m <sup>2</sup>	1.5	83	78	74	70	82	77	73	70	80	76	72	69	78	74	71	69	67	
		2.0	87	83	79	76	86	82	78	76	84	80	77	75	82	79	76	74	72	
取付高さ	器具間隔最大限		2.5	90	86	83	80	88	85	82	79	86	83	81	78	84	82	79	76	
	横方向 (A)	縦方向 (B)	3.0	91	88	85	82	90	87	84	82	88	85	83	81	86	84	82	80	78
H m	1.20 H m	1.20 H m	4.0	93	90	88	86	92	89	87	85	90	88	86	84	88	86	84	83	81
			5.0	94	92	90	88	93	91	89	88	91	89	88	86	89	87	86	85	83
			7.0	95	94	92	91	94	93	92	90	92	91	90	89	90	89	88	87	85
			10.0	96	95	94	93	95	94	93	92	93	92	92	91	91	90	90	89	87

