

# 屋内照明器具特性

品番 (品名)	NNN71500										
光源	NNU140115KLE9 x1 1020.0 lm										
管理番号	K0190792(0)DB1										
BZ分類	BZ2										

器具効率	91%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	91%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.81	0.6	61	52	47	43	60	52	46	43	59	51	46	43	57	50	46	42	41
	中	0.77	0.8	70	62	57	53	69	62	57	53	67	61	56	53	65	60	56	52	51
	否	0.68	1.0	76	69	64	60	75	68	63	60	73	67	63	59	71	66	62	59	57
			1.25	80	74	69	66	79	73	69	66	77	72	68	65	75	71	67	65	63
下方投影面積			1.5	83	78	73	70	82	77	73	70	80	76	72	69	78	74	71	69	67
			2.0	87	83	79	76	86	82	78	75	84	80	77	75	82	79	76	74	72
取付高さ	器具間隔最大限		2.5	89	86	82	80	88	85	82	79	86	83	80	78	84	81	79	77	75
	横方向 (A)	縦方向 (B)	3.0	91	88	85	82	90	87	84	82	87	85	83	81	85	83	81	80	78
Hm	1.19Hm	1.19Hm	4.0	93	90	88	86	92	89	87	85	89	87	86	84	87	86	84	83	81
			5.0	94	92	90	88	93	91	89	87	91	89	87	86	89	87	86	85	83
			7.0	95	94	92	91	94	93	91	90	92	91	90	89	90	89	88	87	85
			10.0	96	95	94	93	95	94	93	92	93	92	91	90	91	90	90	89	86

