

# 屋内照明器具特性

品番 (品名)	NNN71501														
光源	NNU140155KLE9 x1 1610.0 lm														
管理番号	K0190799(0)DB1														
BZ分類	BZ2														

器具効率	93%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	93%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.81	0.6	62	53	47	43	61	53	47	43	60	52	47	43	58	51	46	43	41
	中	0.77	0.8	72	64	58	54	71	63	58	54	69	62	57	54	67	61	57	53	52
	否	0.68	1.0	77	70	65	61	76	70	65	61	74	68	64	61	72	67	63	60	59
			1.25	82	76	71	67	81	75	71	67	79	74	70	67	77	72	69	66	65
下方投影面積			1.5	85	80	75	72	84	79	75	71	82	77	74	71	80	76	73	70	68
	等価発光面積		2.0	89	84	81	78	88	84	80	77	86	82	79	76	83	80	78	76	74
取付高さ	器具間隔最大限		2.5	91	88	84	81	90	87	84	81	88	85	82	80	86	83	81	79	77
	横方向 (A)	縦方向 (B)	3.0	93	90	87	84	92	89	86	84	89	87	85	83	87	85	83	82	80
Hm	1.21Hm	1.21Hm	4.0	95	92	90	88	94	91	89	87	91	89	88	86	89	88	86	85	83
			5.0	96	94	92	90	95	93	91	89	93	91	90	88	91	89	88	87	84
			7.0	97	96	94	93	96	95	93	92	94	93	92	91	92	91	90	89	87
			10.0	98	97	96	95	97	96	95	94	95	94	93	93	93	92	92	91	88

