

屋内照明器具特性

品番 (品名)	NNN71501														
光源	NNU140165KLE9 x1 1450.0 lm														
管理番号	K0190800(0)DB1														
BZ分類	BZ2														

器具効率	93%	天井	80%				70%				50%				30%				0%																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
		床	10%				10%				10%				10%				0%																																	
上方光束	0%	室指数																	照明率 (X0.01)																	ZCM																
下方光束	93%																																																			
保守率	良 中 否	0.81	0.6	63	53	48	44	62	53	47	44	60	52	47	43	58	51	47	43	42																																
		0.77	0.8	72	64	58	54	71	63	58	54	69	62	58	54	67	61	57	54	52																																
			1.0	78	70	65	61	77	70	65	61	74	69	64	61	72	67	64	61	59																																
		0.68	1.25	82	76	71	68	81	75	71	67	79	74	70	67	77	73	69	66	65																																
下方投影面積	c m ²	1.5	85	80	75	72	84	79	75	72	82	77	74	71	80	76	73	70	69																																	
		2.0	89	85	81	78	88	84	80	77	86	82	79	77	84	81	78	76	74																																	
取付高さ	器具間隔最大限		2.5	91	88	84	82	90	87	84	81	88	85	82	80	86	83	81	79	77																																
	横方向 (A)	縦方向 (B)	3.0	93	90	87	84	92	89	86	84	90	87	85	83	87	85	83	82	80																																
H m	1.20 H m	1.20 H m	4.0	95	92	90	88	94	91	89	87	92	90	88	86	89	88	86	85	83																																
			5.0	96	94	92	90	95	93	91	90	93	91	90	88	91	89	88	87	85																																
			7.0	97	96	94	93	96	95	93	92	94	93	92	91	92	91	90	89	87																																
			10.0	98	97	96	95	97	96	95	94	95	94	93	93	93	92	92	91	88																																

