

屋内照明器具特性

品番 (品名)	NNN71501														
光源	NNU141115KLE9 x1 1020.0 lm														
管理番号	K0190806(0)DB1														
BZ分類	BZ2														

器具効率	91%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	91%																			
保守率	良 中 否	0.81	0.6	61	52	47	43	60	52	47	43	59	51	46	43	57	50	46	42	41
		0.77	0.8	70	62	56	52	69	61	56	52	67	60	55	52	65	59	55	52	50
		0.68	1.0	75	68	63	59	74	67	62	59	72	66	62	58	70	65	61	58	56
			1.25	80	73	69	65	79	73	68	65	76	71	67	64	74	70	67	64	62
下方投影面積	c m ²	1.5	83	77	73	69	82	76	72	69	80	75	71	68	77	74	71	68	66	
		2.0	87	82	78	75	86	81	78	75	83	80	77	74	81	78	76	73	72	
取付高さ	器具間隔最大限		2.5	89	85	82	79	88	84	81	79	86	83	80	78	84	81	79	77	75
	横方向 (A)	縦方向 (B)	3.0	91	87	85	82	90	87	84	81	87	85	83	80	85	83	81	79	77
H m	0.72 H m	0.72 H m	4.0	93	90	88	86	92	89	87	85	89	87	86	84	87	86	84	83	81
			5.0	94	92	90	88	93	91	89	87	91	89	87	86	89	87	86	85	82
			7.0	95	94	92	91	94	93	91	90	92	91	90	89	90	89	88	87	85
			10.0	96	95	94	93	95	94	93	92	93	92	91	91	91	90	90	89	87

