

屋内照明器具特性

品番 (品名)	NNN71502	
光源	NNU241105KLE9 x1 2050.0 l m	
管理番号	K0190809 (0) DB 1	
BZ分類	BZ2	

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
		床	10 %				10 %				10 %				10 %				0 %				
上方光束	0 %																						
下方光束	79 %																						
		室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.81	0.6	5.6	4.9	4.5	4.2	5.6	4.9	4.5	4.1	5.4	4.8	4.4	4.1	5.3	4.8	4.4	4.1	4.0			
		0.77	0.8	6.3	5.7	5.2	4.9	6.2	5.6	5.2	4.9	6.1	5.5	5.1	4.9	5.9	5.4	5.1	4.8	4.7			
			1.0	6.7	6.1	5.7	5.4	6.6	6.1	5.7	5.4	6.5	6.0	5.6	5.4	6.3	5.9	5.6	5.3	5.2			
		0.68	1.25	7.1	6.6	6.2	5.9	7.0	6.5	6.1	5.8	6.8	6.4	6.1	5.8	6.6	6.3	6.0	5.8	5.6			
下方投影面積	c m ²	1.5	7.3	6.9	6.5	6.2	7.2	6.8	6.5	6.2	7.0	6.7	6.4	6.1	6.9	6.6	6.3	6.1	5.9				
		2.0	7.6	7.3	6.9	6.7	7.5	7.2	6.9	6.7	7.3	7.1	6.8	6.6	7.2	6.9	6.7	6.5	6.4				
取付高さ	器具間隔最大限		2.5	7.8	7.5	7.2	7.0	7.7	7.4	7.2	7.0	7.5	7.3	7.1	6.9	7.4	7.2	7.0	6.8				
	横方向 (A)	縦方向 (B)	3.0	8.0	7.7	7.4	7.2	7.9	7.6	7.4	7.2	7.7	7.5	7.3	7.1	7.5	7.3	7.2	7.0				
H m	0.74 H m	0.74 H m	4.0	8.1	7.9	7.7	7.5	8.0	7.8	7.6	7.5	7.8	7.7	7.5	7.4	7.7	7.5	7.4	7.3				
			5.0	8.2	8.0	7.9	7.7	8.1	8.0	7.8	7.7	7.9	7.8	7.7	7.6	7.8	7.6	7.5	7.4				
			7.0	8.3	8.2	8.1	8.0	8.2	8.1	8.0	7.9	8.0	7.9	7.8	7.8	7.9	7.8	7.7	7.6				
			10.0	8.4	8.3	8.2	8.1	8.3	8.2	8.1	8.1	8.1	8.1	8.0	7.9	8.0	7.9	7.8	7.7				

