

# 屋内照明器具特性

品番 (品名)	NNN71504				
光源	NNU140115KLE9 x1 1020.0 lm				
管理番号	K0190840(0)DB1				
BZ分類	BZ1/1.8/BZ2				

器具効率	84%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 ( X0.01 )																ZCM	
下方光束	84%																			
保守率	良 中 否	0.81	0.6	61	54	49	46	60	53	49	46	59	53	49	46	57	52	48	46	44
		0.77	0.8	68	62	57	54	67	61	57	54	65	60	56	54	64	59	56	53	52
			1.0	72	67	62	59	71	66	62	59	70	65	61	59	68	64	61	58	57
		0.68	1.25	76	71	67	64	75	70	67	64	73	69	66	63	71	68	65	63	61
下方投影面積	c m <sup>2</sup>	1.5	78	74	70	67	77	73	70	67	75	72	69	66	74	71	68	66	64	
		2.0	81	78	75	72	80	77	74	72	78	76	73	71	77	74	72	70	69	
取付高さ	器具間隔最大限		2.5	83	80	77	75	82	79	77	75	80	78	76	74	78	76	75	73	71
	横方向 (A)	縦方向 (B)	3.0	85	82	79	77	84	81	79	77	82	79	78	76	80	78	76	75	73
H m	1.09 H m	1.09 H m	4.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	78	76
			5.0	87	85	84	82	86	84	83	82	84	83	81	80	82	81	80	79	77
			7.0	88	87	86	84	87	86	85	84	85	84	83	82	83	83	82	81	79
			10.0	89	88	87	86	88	87	86	85	86	85	85	84	84	84	83	82	80

