

屋内照明器具特性	
品番 (品名)	LGB87030Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0171430(0)DB1
BZ分類	BZ8/4.5/BZ7

器具効率	73%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	37%	床	10%				10%				10%				10%				0%	
下方光束	36%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	3.3	2.4	1.8	1.4	3.0	2.2	1.7	1.3	2.5	1.8	1.4	1.1	2.0	1.5	1.1	9	5	
	中 0.6	0.8	3.9	3.0	2.4	2.0	3.6	2.8	2.2	1.8	2.9	2.3	1.9	1.6	2.4	1.9	1.5	13	8	
	否 0.56	1.0	4.3	3.5	2.9	2.4	4.0	3.2	2.7	2.2	3.3	2.7	2.2	1.9	2.6	2.2	1.8	16	10	
下方投影面積	cm ²	1.25	4.7	3.9	3.4	2.9	4.3	3.6	3.1	2.7	3.6	3.0	2.6	2.3	2.9	2.5	2.2	19	12	
		1.5	5.0	4.3	3.7	3.3	4.6	4.0	3.4	3.0	3.8	3.3	2.9	2.6	3.1	2.7	2.4	21	14	
等価発光面積	cm ²	2.0	5.4	4.8	4.3	3.8	5.0	4.4	4.0	3.6	4.2	3.7	3.4	3.0	3.4	3.1	2.8	25	17	
		2.5	5.7	5.1	4.7	4.3	5.2	4.7	4.3	4.0	4.4	4.0	3.7	3.4	3.6	3.3	3.0	28	19	
取付高さ	器具間隔最大限		3.0	5.9	5.4	5.0	4.6	5.4	5.0	4.6	4.3	4.6	4.2	3.9	3.6	3.7	3.5	32	21	
H _m	横方向 (A)	縦方向 (B)	4.0	6.1	5.7	5.4	5.0	5.7	5.3	5.0	4.7	4.8	4.5	4.2	4.0	3.9	3.7	3.5	33	23
	1.60H _m	1.81H _m	5.0	6.3	5.9	5.6	5.3	5.8	5.5	5.2	5.0	4.9	4.7	4.5	4.2	4.1	3.9	3.7	3.5	25
			7.0	6.5	6.2	6.0	5.7	6.0	5.8	5.5	5.3	5.1	4.9	4.7	4.6	4.2	4.1	4.0	3.8	27
			10.0	6.6	6.4	6.2	6.0	6.2	6.0	5.8	5.6	5.3	5.1	5.0	4.8	4.4	4.3	4.2	4.1	2.9

