

# 屋内照明器具特性

品番 (品名) **LGB81010**

光源 **LLD5010LCC1 ×1** **1095.0 1m**

管理番号 **K0190453(0)DR1**

BZ分類 **BZ1**

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	2%	反射率	壁	10%				10%				10%				10%				0%
下方光束	98%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	83	77	73	71	82	77	73	71	81	76	73	70	80	75	72	70	69	
	中 0.63	0.8	89	83	79	76	88	83	79	76	86	81	78	76	84	80	78	75	74	
	否 0.56	1.0	92	87	83	81	91	86	83	80	89	85	82	80	87	84	81	79	78	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	95	90	87	84	94	90	86	84	92	88	85	83	90	87	84	82	81	
		1.5	97	93	90	87	96	92	89	86	93	90	88	86	91	89	87	85	83	
		2.0	99	96	93	91	98	95	92	90	96	93	91	89	94	91	90	88	86	
取付高さ	器具間隔最大限		2.5	101	98	96	93	100	97	95	93	97	95	93	91	95	93	92	90	88
	横方向 (A)	縦方向 (B)	3.0	102	100	97	95	101	98	96	95	98	96	95	93	96	94	93	92	89
Hm	0.80Hm	0.82Hm	4.0	103	101	100	98	102	100	99	97	100	98	97	95	97	96	95	94	91
			5.0	104	103	101	100	103	101	100	99	100	99	98	97	98	97	96	95	92
			7.0	105	104	103	102	104	103	102	101	101	100	100	99	99	98	97	97	94
			10.0	106	105	104	103	105	104	103	102	102	101	101	100	100	99	98	98	95

