

屋内照明器具特性

品番 (品名)	LGB81010	
光源	LLD5020LCC1 x1	1085.0 lm
管理番号	K0190454(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 3%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	97%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良	0.67	0.6	77	70	65	62	76	69	65	62	74	68	64	61	73	68	64	61	60
	中	0.63	0.8	84	77	72	69	83	76	72	69	81	75	71	68	79	74	71	68	66
	否	0.56	1.0	88	82	77	74	87	81	77	74	85	80	76	73	82	78	75	72	71
下方投影面積	等価発光面積	cm ²	1.25	92	86	82	79	90	85	81	78	88	84	80	77	86	82	79	77	75
			1.5	94	89	85	82	93	88	85	82	90	86	83	81	88	85	82	80	78
取付高さ	器具間隔最大限		2.0	97	93	90	87	96	92	89	86	93	90	87	85	91	88	86	84	82
	横方向 (A)	縦方向 (B)	2.5	99	96	93	90	98	95	92	90	95	92	90	88	93	90	88	87	84
Hm	0.42Hm	0.41Hm	3.0	101	98	95	93	99	96	94	92	96	94	92	90	94	92	90	89	86
			4.0	102	100	98	96	101	99	97	95	98	96	95	93	95	94	93	91	88
			5.0	103	101	100	98	102	100	99	97	99	98	96	95	96	95	94	93	90
			7.0	105	103	102	101	103	102	101	99	100	99	98	97	98	97	96	95	92
			10.0	106	105	104	103	104	103	102	101	101	100	100	99	98	98	97	97	93

