

屋内照明器具特性

品番 (品名)	LGB81011	
光源	LLD5010LCC1 ×1	1095.0 1m
管理番号	K0190456(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 2%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束 98%		床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	83	77	74	71	83	77	73	71	81	76	73	70	80	75	72	70	69	
	中 0.63	0.8	89	83	79	77	88	83	79	76	86	82	78	76	84	81	78	76	74	
	否 0.56	1.0	92	87	83	81	91	86	83	80	89	85	82	80	87	84	81	79	78	
下方投影面積 等価発光面積	cm ²	1.25	95	91	87	84	94	90	87	84	92	88	86	83	90	87	85	83	81	
		1.5	97	93	90	87	96	92	89	87	94	90	88	86	92	89	87	85	83	
取付高さ Hm	器具間隔最大限		2.5	101	98	96	94	100	97	95	93	97	95	93	92	95	93	92	90	88
	横方向 (A)	縦方向 (B)	3.0	102	100	97	95	101	99	97	95	98	96	95	93	96	94	93	92	89
Hm	0.80Hm	0.81Hm	4.0	104	102	100	98	102	100	99	97	100	98	97	96	97	96	95	94	91
			5.0	104	103	101	100	103	102	100	99	100	99	98	97	98	97	96	95	92
			7.0	105	104	103	102	104	103	102	101	101	100	100	99	99	98	97	97	94
			10.0	106	105	104	104	105	104	103	102	102	101	101	100	100	99	99	98	95

