

屋内照明器具特性

品番 (品名)	LGD9201									
光源	LLD5000LCC1 ×1					1140.0 1 m				
管理番号	K0190378 (0) DR1									
BZ分類	BZ3									

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	99 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	64	53	47	42	63	53	46	42	60	52	46	42	59	51	46	42	40		
		0.8	74	64	58	53	72	64	58	53	70	62	57	53	68	61	56	52	51		
		1.0	80	71	65	61	79	71	65	61	76	69	64	60	74	68	63	60	58		
		1.25	85	78	72	68	84	77	72	67	81	75	71	67	79	74	70	66	64		
下方投影面積	c m ²	1.5	89	82	77	72	87	81	76	72	85	79	75	72	82	78	74	71	69		
		2.0	93	88	83	79	92	87	83	79	89	85	81	78	87	83	80	77	75		
取付高さ	器具間隔最大限		2.5	96	91	87	84	95	90	87	83	92	88	85	82	90	86	84	81	79	
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	96	93	89	87	94	91	88	85	91	89	86	84	82	
H m	1.25 H m	1.25 H m	4.0	100	97	94	92	99	96	93	91	96	94	92	90	94	92	90	88	86	
			5.0	102	99	97	94	100	98	96	94	98	96	94	92	95	94	92	91	88	
			7.0	103	101	99	98	102	100	98	97	99	98	96	95	97	96	95	94	91	
			10.0	104	103	102	100	103	102	101	99	101	100	99	98	98	97	97	96	93	

