

# 屋内照明器具特性

品番 (品名)	LGS9000									
光源	LLD5000LCC1 ×1					1140.0 1 m				
管理番号	K0190447 ( 0 ) DR 1									
BZ分類	BZ3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	3 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	97 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	64	53	46	42	62	53	46	42	60	51	46	41	58	50	45	41	39
	中	0.63	0.8	74	64	58	53	72	63	57	53	70	62	56	52	67	61	56	52	50
	否	0.56	1.0	80	71	65	61	79	71	65	60	76	69	64	60	73	67	63	59	57
			1.25	85	78	72	68	84	77	71	67	81	75	70	66	78	73	69	66	63
下方投影面積	cm <sup>2</sup>		1.5	89	82	77	72	87	81	76	72	84	79	75	71	81	77	73	70	68
等価発光面積	cm <sup>2</sup>		2.0	93	88	83	79	92	87	82	79	89	84	81	78	86	82	79	76	74
取付高さ	器具間隔最大限		2.5	96	91	87	84	95	90	86	83	92	88	85	82	89	86	83	81	78
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	96	93	89	86	93	90	87	85	91	88	86	83	80
Hm	1.25Hm	1.25Hm	4.0	100	97	94	92	99	96	93	91	96	93	91	89	93	91	89	87	84
			5.0	102	99	97	94	100	98	96	93	97	95	93	92	94	93	91	90	86
			7.0	103	101	100	98	102	100	98	97	99	97	96	95	96	95	94	93	89
			10.0	105	103	102	101	103	102	101	99	100	99	98	97	97	97	96	95	91

