

# 屋内照明器具特性

品番 (品名)	LGS9001	
光源	LLD5020LCC1 ×1	1085.0 lm
管理番号	K0190452(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 4%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																	ZCM		
保守率	良 0.67	0.6	77	70	65	62	76	69	65	61	74	68	64	61	72	67	63	61	59	
	中 0.63		84	77	72	69	82	76	72	69	80	75	71	68	78	74	70	68	66	
	否 0.56		88	82	77	74	87	81	77	73	84	79	76	73	82	78	75	72	70	
下方投影面積	cm <sup>2</sup>	1.25	91	86	82	78	90	85	81	78	88	83	80	77	85	82	79	76	74	
		1.5	94	89	85	82	93	88	84	81	90	86	83	80	87	84	82	79	77	
等価発光面積	cm <sup>2</sup>	2.0	97	93	90	87	96	92	89	86	93	90	87	85	90	88	85	84	81	
		2.5	99	96	93	90	98	94	92	89	95	92	90	88	92	90	88	86	84	
取付高さ	器具間隔最大限		3.0	101	97	95	92	99	96	94	92	96	94	92	90	93	91	90	88	85
	横方向 (A)	縦方向 (B)	4.0	102	100	98	96	101	98	96	95	98	96	94	93	95	93	92	91	88
Hm	0.42Hm	0.41Hm	5.0	103	101	99	98	102	100	98	97	99	97	96	95	96	95	94	93	89
			7.0	104	103	102	100	103	102	100	99	100	99	98	97	97	96	95	95	91
			10.0	105	104	103	102	104	103	102	101	101	100	99	99	98	97	97	96	93

