

# 屋内照明器具特性

|         |                  |  |  |  |  |           |  |  |  |  |
|---------|------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | NNN74500K        |  |  |  |  |           |  |  |  |  |
| 光源      | NNU240115KLE9 x1 |  |  |  |  | 1840.0 lm |  |  |  |  |
| 管理番号    | K0190844(1)DB1   |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ2              |  |  |  |  |           |  |  |  |  |

|        |                                     |          |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|-------------------------------------|----------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 79%                                 | 天井       | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |                                     | 壁        | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%                                  | 床        | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 79%                                 | 室指数      | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良<br>中<br>否<br>0.77<br>0.72<br>0.68 | 0.6      | 54            | 46 | 42 | 38 | 53  | 46 | 41 | 38 | 52  | 45 | 41 | 38 | 50  | 45 | 41 | 38 | 37  |    |
|        |                                     | 0.8      | 62            | 55 | 50 | 47 | 61  | 54 | 50 | 47 | 59  | 53 | 49 | 46 | 57  | 53 | 49 | 46 | 45  |    |
|        |                                     | 1.0      | 66            | 60 | 56 | 53 | 65  | 60 | 56 | 52 | 64  | 59 | 55 | 52 | 62  | 58 | 55 | 52 | 51  |    |
|        |                                     | 1.25     | 70            | 65 | 61 | 58 | 69  | 64 | 61 | 58 | 67  | 63 | 60 | 57 | 66  | 62 | 59 | 57 | 55  |    |
| 下方投影面積 | c m <sup>2</sup>                    | 1.5      | 73            | 68 | 64 | 61 | 72  | 67 | 64 | 61 | 70  | 66 | 63 | 61 | 68  | 65 | 62 | 60 | 59  |    |
|        |                                     | 2.0      | 76            | 72 | 69 | 67 | 75  | 72 | 69 | 66 | 73  | 70 | 68 | 66 | 72  | 69 | 67 | 65 | 63  |    |
| 取付高さ   | 器具間隔最大限                             |          | 2.5           | 78 | 75 | 72 | 70  | 77 | 74 | 72 | 70  | 75 | 73 | 71 | 69  | 73 | 71 | 70 | 68  | 66 |
|        | 横方向 (A)                             | 縦方向 (B)  | 3.0           | 80 | 77 | 74 | 72  | 79 | 76 | 74 | 72  | 77 | 74 | 73 | 71  | 75 | 73 | 71 | 70  | 68 |
| H m    | 1.12 H m                            | 1.12 H m | 4.0           | 81 | 79 | 77 | 75  | 80 | 78 | 76 | 75  | 78 | 77 | 75 | 74  | 76 | 75 | 74 | 73  | 71 |
|        |                                     |          | 5.0           | 82 | 80 | 79 | 77  | 81 | 80 | 78 | 77  | 79 | 78 | 77 | 75  | 77 | 76 | 75 | 74  | 72 |
|        |                                     |          | 7.0           | 83 | 82 | 81 | 80  | 82 | 81 | 80 | 79  | 80 | 79 | 78 | 78  | 79 | 78 | 77 | 76  | 74 |
|        |                                     |          | 10.0          | 84 | 83 | 82 | 81  | 83 | 82 | 81 | 81  | 81 | 81 | 80 | 79  | 79 | 79 | 78 | 78  | 76 |

