

屋内照明器具特性

品番 (品名)	LGB15392														
光源	LLD5000LCC1 ×1 1140.0 1 m														
管理番号	K0190384 (0) DR 1														
BZ分類	BZ1 / 8.5 / BZ2														

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	68 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)															ZCM		
保守率	良 中 否	0.67	0.6	56	52	49	47	55	51	49	47	54	51	48	47	53	50	48	47	46
		0.63	0.8	60	56	53	51	59	56	53	51	58	55	53	51	57	55	53	51	50
			1.0	62	59	56	55	62	58	56	54	61	58	56	54	59	57	55	54	53
		0.56	1.25	64	61	59	57	64	61	59	57	62	60	58	57	61	59	58	56	55
下方投影面積	c m ²	1.5	66	63	61	59	65	62	60	59	64	62	60	58	62	61	59	58	57	
		2.0	67	65	63	62	67	65	63	61	65	63	62	61	64	63	61	60	59	
取付高さ	器具間隔最大限		2.5	68	66	65	63	68	66	64	63	66	65	63	62	65	64	63	62	60
	横方向 (A)	縦方向 (B)	3.0	69	67	66	64	68	67	65	64	67	66	64	63	66	64	63	63	61
H m	0.81 H m	0.81 H m	4.0	70	69	67	66	69	68	67	66	68	67	66	65	66	65	65	64	62
			5.0	70	69	68	67	70	69	68	67	68	67	66	66	67	66	65	65	63
			7.0	71	70	69	68	70	69	69	68	69	68	67	67	67	67	66	66	64
			10.0	71	71	70	69	71	70	69	69	69	69	68	67	68	67	67	66	64

