

# 屋内照明器具特性

品番 (品名) **LGB15392**

光源 **LLD5020LCC1 x1** **1085.0** lm

管理番号 **K0190386(0)DR1**

BZ分類 **BZ1**

器具効率	82%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	82%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	71	66	63	61	70	66	63	61	69	65	63	61	68	65	63	61	60	
	中 0.63	0.8	75	71	68	66	75	71	68	66	73	70	68	66	72	70	67	66	65	
	否 0.56	1.0	78	74	72	70	77	74	71	70	76	73	71	69	75	72	70	69	68	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	80	77	75	73	79	76	74	72	78	75	74	72	77	75	73	72	71	
		1.5	81	79	77	75	81	78	76	74	79	77	75	74	78	76	75	73	72	
取付高さ	器具間隔最大限		2.0	83	81	79	78	83	80	79	77	81	79	78	77	80	78	77	76	
	横方向 (A)	縦方向 (B)	2.5	84	82	81	79	84	82	80	79	82	81	79	78	81	79	78	77	
Hm	0.44Hm	0.44Hm	3.0	85	83	82	81	84	83	81	80	83	81	80	79	81	80	79	77	
			4.0	86	85	84	83	85	84	83	82	83	83	82	81	82	81	80	78	
			5.0	87	86	85	84	86	85	84	83	84	83	82	82	82	82	81	79	
			7.0	87	86	86	85	86	86	85	84	85	84	83	83	83	82	82	80	
			10.0	88	87	87	86	87	86	86	85	85	85	84	84	83	83	83	80	

