

# 屋内照明器具特性

品番 (品名) **LGB16702**

光源 **LLD5010LCC1 x1** **1095.0 lm**

管理番号 **K0190385(0)DR1**

BZ分類 **BZ1**

器具効率	85%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	85%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良 0.67	0.6	79	75	73	71	78	75	73	71	77	74	73	71	76	74	72	71	70	
	中 0.63	0.8	82	79	77	75	81	78	76	75	80	78	76	75	79	77	76	74	74	
	否 0.56	1.0	84	81	79	77	83	81	79	77	82	80	78	77	81	79	78	77	76	
下方投影面積	cm <sup>2</sup>	1.25	85	83	81	80	85	82	81	79	83	82	80	79	82	81	80	79	78	
		1.5	86	84	83	81	86	84	82	81	84	83	81	80	83	82	81	80	79	
等価発光面積	cm <sup>2</sup>	2.0	88	86	85	83	87	85	84	83	86	84	83	82	84	83	82	81	80	
		2.5	89	87	86	85	88	86	85	84	86	85	84	83	85	84	83	82	81	
取付高さ	器具間隔最大限		3.0	89	88	87	86	88	87	86	85	87	86	85	84	85	85	84	83	82
	横方向 (A)	縦方向 (B)	4.0	90	89	88	87	89	88	87	87	87	86	85	86	85	85	84	83	82
Hm	0.82Hm	0.82Hm	5.0	90	89	89	88	89	89	88	87	88	87	87	86	86	86	85	85	83
			7.0	91	90	90	89	90	89	89	88	88	88	87	87	86	86	86	86	86
			10.0	91	91	90	90	90	90	89	88	88	88	88	87	87	86	86	84	

