

屋内照明器具特性	
品番 (品名)	LGB15393
光源	LLD5000LCC1 ×1 1140.0 1m
管理番号	K0190387(0)DR1
BZ分類	BZ1

器具効率	50%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	4.3	4.1	3.9	3.8	4.3	4.1	3.9	3.8	4.2	4.0	3.9	3.8	4.2	4.0	3.9	3.8	3.7
	中	0.63	0.8	4.6	4.4	4.2	4.1	4.6	4.3	4.2	4.1	4.5	4.3	4.2	4.1	4.4	4.3	4.1	4.0	4.0
	否	0.56	1.0	4.7	4.5	4.4	4.3	4.7	4.5	4.4	4.3	4.6	4.5	4.3	4.2	4.6	4.4	4.3	4.2	4.2
			1.25	4.9	4.7	4.5	4.4	4.8	4.7	4.5	4.4	4.7	4.6	4.5	4.4	4.7	4.5	4.4	4.4	4.3
下方投影面積	c m ²		1.5	5.0	4.8	4.6	4.5	4.9	4.7	4.6	4.5	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.5	4.4
	等価発光面積		c m ²	2.0	5.1	4.9	4.8	4.7	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.6
取付高さ	器具間隔最大限		2.5	5.1	5.0	4.9	4.8	5.1	4.9	4.8	4.8	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.7	4.6
	横方向 (A)	縦方向 (B)	3.0	5.1	5.0	4.9	4.9	5.1	5.0	4.9	4.8	5.0	4.9	4.8	4.8	4.9	4.8	4.8	4.7	4.6
H m	0.88 H m	0.88 H m	4.0	5.2	5.1	5.0	4.9	5.1	5.1	5.0	4.9	5.0	5.0	4.9	4.8	4.9	4.9	4.8	4.8	4.7
			5.0	5.2	5.1	5.1	5.0	5.2	5.1	5.0	5.0	5.1	5.0	4.9	4.9	5.0	4.9	4.9	4.8	4.7
			7.0	5.3	5.2	5.1	5.1	5.2	5.1	5.1	5.0	5.1	5.0	5.0	4.9	5.0	4.9	4.9	4.9	4.7
			10.0	5.3	5.2	5.2	5.1	5.2	5.2	5.1	5.1	5.1	5.1	5.0	5.0	5.0	5.0	4.9	4.9	4.8

