

屋内照明器具特性

品番 (品名) **LGB15393**

光源 **LLD5020LCC1 ×1** **1085.0 l m**

管理番号 **K0190389 (0) DR 1**

BZ分類 **BZ1**

器具効率	74 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	74 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	65	62	59	58	65	61	59	58	64	61	59	58	63	61	59	57	57	
	中 0.63	0.8	69	66	64	62	68	65	63	62	67	65	63	62	67	64	63	61	61	
	否 0.56	1.0	71	68	66	65	71	68	66	64	69	67	66	64	68	67	65	64	63	
下方投影面積	c m ²	1.25	73	70	68	67	72	70	68	67	71	69	68	66	70	68	67	66	65	
		1.5	74	72	70	69	73	71	70	68	72	70	69	68	71	70	68	67	66	
等価発光面積	c m ²	2.0	75	74	72	71	75	73	72	71	73	72	71	70	72	71	70	69	68	
		2.5	76	75	73	72	76	74	73	72	74	73	72	71	73	72	71	70	69	
取付高さ	器具間隔最大限		3.0	77	76	74	73	76	75	74	73	75	74	73	72	73	73	72	71	70
	横方向 (A)	縦方向 (B)	4.0	78	77	76	75	77	76	75	74	75	75	74	73	74	73	73	72	71
H _m	0.43 H _m	0.43 H _m	5.0	78	77	76	76	77	76	76	75	76	75	74	74	74	74	73	73	71
			7.0	78	78	77	77	78	77	77	76	76	76	75	75	75	74	74	74	72
			10.0	79	78	78	77	78	78	77	77	76	76	76	75	75	75	74	74	72

