

# 屋内照明器具特性

品番 (品名) **LGB15398**

光源 **LLD5010LCC1 ×1**      **1095.0** l m

管理番号 **K0190391 (1) DR 1**

BZ分類 **BZ1**

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	89 %		壁	10 %				10 %				10 %				10 %				
		室指数	照明率 ( X0.01)																ZCM	
保守率	良 0.67	0.6	79	74	72	70	78	74	71	70	77	74	71	69	76	73	71	69	68	
	中 0.63	0.8	83	79	76	74	82	79	76	74	81	78	76	74	80	77	75	74	73	
	否 0.56	1.0	85	82	79	78	85	82	79	77	83	81	79	77	82	80	78	77	76	
下方投影面積	c m <sup>2</sup>	1.25	88	84	82	80	87	84	82	80	85	83	81	80	84	82	81	79	78	
		1.5	89	86	84	82	88	86	84	82	87	85	83	81	85	84	82	81	80	
等価発光面積	c m <sup>2</sup>	2.0	91	88	87	85	90	88	86	85	88	87	85	84	87	85	84	83	82	
		2.5	92	90	88	87	91	89	88	86	89	88	87	86	88	87	86	85	83	
取付高さ	器具間隔最大限		3.0	92	91	89	88	92	90	89	88	90	89	88	87	88	87	86	84	
H m	0.85 H m	0.85 H m	4.0	93	92	91	90	92	91	90	89	91	90	89	88	89	88	88	87	85
			5.0	94	93	92	91	93	92	91	90	91	90	90	89	89	89	89	88	88
			7.0	95	94	93	92	94	93	92	92	92	91	91	90	90	89	89	87	
			10.0	95	94	94	94	94	94	93	93	92	92	91	91	90	90	89	87	

